

■ General

Many KREIDEZEIT wall paints are specially formulated as powder and are only mixed with water on site shortly before processing. On the one hand the transport weight and thus also the CO₂ emissions during transport to our customers are reduced, on the other hand we can completely dispense with the use of preservatives. The latter makes them interesting for many allergy sufferers, but also brings with it only a limited shelf life of the mixed colors, usually only 1 to a few days.

In many cases, however, it is necessary to finish a project in several time intervals. Constant remixing, especially of colour tones, can be impractical here. Pinol serves to prolong the durability of these paints, which are ready mixed with water, so that service lives of up to many weeks are possible in which the paints can be used up. The actual service life of a mixture cannot be guaranteed and also depends on other influences. Storage of the mixtures at cool temperatures, use of clean water and clean tools (buckets, stirrers, brushes/rollers) significantly prolongs the shelf life.

■ Uses

As additive to KREIDEZEIT Casein Marble Paint, Vega Wallpaint, Clay Paint, Brush- and Roll.on Plaster, Tempera Paint.

■ Composition

Pine Oil, Orange Oil

■ Application

Recommended quantity: 5 ml Pinol per 1 kg Kreidezeit Wall paint (powder)

First mix the Kreidezeit wall paint with water according to the instructions, note the soaking time and stir again. Then stir in Pinol thoroughly for 1-2 minutes. Finished.

Never store mixed paint in open containers, but close them airtight. Additional covering of the paint surface with plastic foil prevents possible crust formation.

The condition of the mixture must be checked before further processing after a longer storage period. Do not use bad or foul smelling paint under any circumstances: Danger of prolonged odour problems even after drying!

Pinol is a natural essential oil with a pleasant characteristic odour which usually disappears after 1 to a few weeks on painted walls.

■ Container Sizes

Article no. 259 50 ml

For prices, please refer to the valid price list.

■ Storage

Shelf life approx. 2 years if unopened. Always keep opened containers hermetically closed.

■ Warning

Pay attention to possible natural substance allergies. The natural raw materials used produce a typical product smell! Keep out of reach of children.

■ Disposing Leftover Product

Do not discharge product residues into the waste water, but keep them airtightly sealed and use them later. Put completely emptied containers into the collection of recyclables. The current official regulations for the disposal of paint and paint residues must be observed.



■ Hazard statements

- H226: Flammable liquid and vapour.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H411: Toxic to aquatic life with long lasting effects.
- EUH 208: Contains orange oil. May produce an allergic reaction.

■ Precautionary statements

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P262 Do not get in eyes, on skin, or on clothing.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P331 Do NOT induce vomiting.
- P332+P313 If skin irritation occurs: Get medical advice/ attention.
- P363 Wash contaminated clothing before reuse.
- P405 Store locked up.
- P501 Dispose of contents/container to special disposal.

The information above was determined based on our most recent experiences. Due to processing methods and environmental influences, as well as the varying nature of the substrates, liability for the general validity of the individual recommendations is excluded. Users must test the product prior to application to ensure it is fit for the designated purpose (sample coating).

This document is no longer valid if a new version is published or the product is modified. For the latest product information, please contact Kreidezeit directly or visit our website at www.kreidezeit.de